

SPEC

HEAVY DUTY



- ◆ LOW OPERATING COSTS
- ◆ NO USE OF WATER
- ◆ DRY ICE
- ◆ NON TOXIC
- ◆ EASY TO OPERATE
- ◆ HIGH POWER PRESSURE

SPECCO2 - PROi

SPECCO2-PROi



TECHNICAL DATA:

Dimension W x D x H:	650 x 550 x 950 mm
Weight:	70 kg
Air flow range:	0.8 -9 m ³ /min.
Blast pressure range:	2-14 bar
Tank capacity:	25 kg
Pellet consumption:	0 – 75 kg/hour (variable)
Power supply:	110V-230V / AC 50-60 Hz
Air quality:	Dry and free of oil and particles
Noise:	60-120 dB (A) depending on nozzle and pressure

STANDARD EQUIPMENT:

Adjustment of air pressure Adjustment of pellet

consumption Safety switch



Blasting gun: · Ice/Granulate
Blasting hose: · 5 m 3/4" incl. quick safety coupling
· Electrical connection

· Protective sleeve
Air supply hose: 10 m 3/4" incl. claw coupling

Electrical cord: 10 m

Nozzle: Ø7 mm Standard plastic round
Standard round nozzle (customer choice)

OPTIONAL:

- Wide range of round, flat and bended nozzles
- Wide range of special nozzles

SPEC



SPEC CONSULTING PTE. LTD 50 GOLDHILL PLAZA
#21-02/06, SINGAPORE, 308900



info@specco2.com

