

SPEC

HEAVY DUTY



- ◆ LOW OPERATING COSTS
- ◆ NO USE OF WATER
- ◆ DRY ICE
- ◆ NON TOXIC
- ◆ EASY TO OPERATE
- ◆ HIGH POWER PRESSURE

SPECCO2-MINI

SPECCO2-MINI



TECHNICAL DATA:

Dimension W x D x H:	410 x 470 x 480 mm
Weight:	26 kg
Air flow range:	0,6 - 3 m ³ /min.
Blast pressure range:	2-10 bar
Tank capacity:	8 kg
Pellet consumption:	25 kg/hour.
Power supply:	110V-230V / AC 50-60 Hz
Air quality:	Dry and free of oil and particles
Noise:	60-120 dB (A) depending on nozzle and pressure

STANDARD EQUIPMENT:

Blasting hose:	· 5 m w. quick safety coupling · Electrical connection · Protective sleeve
Electrical cord:	10 m
Antistatic cord:	3 m
Air supply hose:	10 m 1/2" incl. coupling
Nozzle:	Ø7 mm Standard plastic round <i>Standard round nozzle (customer choice)</i>

OPTIONAL:

- Wide range of round, flat and bended nozzles
- Wide range of special nozzles
- External pressure regulator

SPEC



SPEC CONSULTING PTE. LTD 50 GOLDHILL PLAZA
#21-02/06, SINGAPORE, 308900



info@specco2.com

